



Blue Power Tools

The Colour of Innovation

Range 2014

For professionals from professionals



BOSCH

Invented for life

GBM 600 Professional
Rotary Drill


Technical data	
Part number	0 601 1A4 0K0
Power input	320 W
No-load speed	0 - 4200 min ⁻¹
Rated speed	0 - 1500 min ⁻¹
Chuck capacity	0.5 - 6.5 mm
Drilling dia. in steel	6.5 mm
Drilling dia. in aluminium	6.5 mm
Drilling dia. in wood	13 mm
Weight	1 kg

GBM 6 Professional
Rotary Drill


Technical data	
Part number	0 601 472 0F0
Power input	350 W
No-load speed	4000 rpm
Chuck capacity	0.5 - 6.5 mm
Drilling dia. in steel	6.5 mm
Drilling dia. in aluminium	6 mm
Drilling dia. in wood	15 mm
Drill spindle connecting thread	3/8" - 24 UNF
Weight	1.1 kg

GBM 10 RE Professional
Rotary Drill


Technical data	
Part number	0 601 473 5F0
Power input	450 W
No-load speed	0 - 2600 rpm
Chuck capacity	1 - 10 mm
Drilling dia. in steel	10 mm
Drilling dia. in aluminium	10 mm
Drilling dia. in wood	25 mm
Drill spindle connecting thread	3/8" - 24 UNF
Weight	1.5 kg

GBM 13 RE Professional
Rotary Drill


Technical data	
Part number	0 601 477 5F0
Power input	600 W
No-load speed	0 - 2600 rpm
Chuck capacity	1.5 - 13 mm
Drilling dia. in steel	13 mm
Drilling dia. in aluminium	13 mm
Drilling dia. in wood	30 mm
Drill spindle connecting thread	1/2" - 20UNF
Weight	1.7 kg

GBM 13-2 Professional
Rotary Drill


Technical data	
Part number	0 601 169 055
Power input	550 W
No-load speed	0 - 1000/1900 rpm
Chuck capacity	1 - 13 mm
Drilling dia. in steel	13 / 8 mm
Drilling dia. in aluminium	20 / 12 mm
Drilling dia. in wood	32 / 20 mm
Drill spindle connecting thread	1/2" - 20 UNF
Weight	1.9 kg

GBM 23-2 Professional
Rotary Drill


Technical data	
Part number	0 601 121 103
Power input	1150 W
Drilling dia. in steel	23 / 13 mm
Drilling dia. in aluminium	28 / 18 mm
Drilling dia. in wood	50 / 35 mm
Drill spindle connecting thread	MK 2 - DIN 228
Weight	4.8 kg

GBM 32-4 Professional
Rotary Drill


Technical data	
Part number	0 601 130 203
Power input	1500 W
No-load speed	210 / 330 / 470 / 740 rpm
Drilling dia. in steel	32 mm
Drilling dia. in aluminium	50 mm
Drilling dia. in wood	70 mm
Drill spindle connecting thread	MK 3 - DIN 228
Weight	7.3 kg

GMB 32 Professional
Magnetic Drill Stand


Technical data	
Part number	0 601 193 003
Magnet retention force	25 kN
Clamping flange diameter	65 mm
Working length, Z-axis	223 mm
Twist drill bit diameter	32 mm
Weight	1.5 kg

GSR 6-25 TE Professional
Screwdriver


Technical data	
Part number	0 601 445 000
Power input	1500 W
Self-drilling screw diameter	6.0 mm
No-load speed	0 - 2500 rpm
Torque, max. (soft screwdriving applications)	20 Nm
Toolholder	1/4" internal hexagon
Weight	1.5 kg

GDS 30 Professional
Impact Wrench


Technical data	
Part number	0 601 435 103
Power input	920 W
Screw diameter	M 30max. M 30
Torque, max. (hard screwdriving applications)	1000 Nm
Torque, max. (soft screwdriving applications)	500 Nm
Toolholder	1" external square
Rated speed	860 rpm
Weight	7.3 kg

GDS 18 E Professional**Impact Wrench**

Technical data	
Part number	0 601 444 000
Power input	500 W
Rated speed	500 - 1300 rpm
Screw diameter	M 6 - M 18
Torque, max. (hard screwdriving applications)	250 Nm
Torque, max. (soft screwdriving applications)	160 Nm
Toolholder	1/2" external square
Weight	3.2 kg

GSB 10 Professional**Impact Drill**

Technical data	
Part number	0 601 216 0K4
Power input	500 W
No-load speed	2600 rpm
Impact rate at no-load speed	41600 bpm
Drilling dia. in concrete	10 mm
Drilling dia. in steel	8 mm
Drilling dia. in wood	20 mm
Chuck capacity	1 - 10 mm
Weight	1.5 kg

GSB 10 RE Professional**Impact Drill**

Technical data	
Part number	0 601 216 1F3
Power input	500 W
No-load speed	0 - 2600 rpm
Impact rate at no-load speed	0 - 41600 bpm
Drilling dia. in concrete	10 mm
Drilling dia. in steel	8 mm
Drilling dia. in wood	20 mm
Chuck capacity	1 - 10 mm
Weight	1.5 kg

GSB 13 RE Professional**Impact Drill**

Technical data	
Part number	0 601 217 1F3
Power input	600 W
No-load speed	0 - 2800 rpm
Impact rate at no-load speed	0 - 44800 bpm
Drilling dia. in concrete	13 mm
Drilling dia. in steel	10 mm
Drilling dia. in wood	25 mm
Chuck capacity	1.5 - 13 mm
Weight	1.7 kg

GSB 1300 Professional**Impact Drill**

Technical data	
Part number	0 601 1A1 0K1
Power input	550 W
No-load speed	0 - 2700 rpm
Impact rate at no-load speed	0 - 41600 bpm
Drilling dia. in concrete	13 mm
Drilling dia. in steel	10 mm
Drilling dia. in wood	25 mm
Chuck capacity	1.5 - 13 mm
Weight	1.8 kg

GSB 16 RE Professional**Impact Drill**

Technical data	
Part number	0 601 218 1K0
Power input	701 W
No-load speed	0 - 3000 rpm
Impact rate at no-load speed	0-48000 bpm
Drilling dia. in concrete	16 mm
Drilling dia. in steel	12 mm
Drilling dia. in wood	30 mm
Chuck capacity	1.5 - 13 mm
Weight	1.9 kg

GSB 20-2 RE Professional**Impact Drill**

Technical data	
Part number	0 601 184 655
Power input	701 W
No-load speed	0 - 1000/3000 rpm
Impact rate at no-load speed	0 - 16000/48000 bpm
Drilling dia. in concrete	20 / 13 mm
Drilling dia. in steel	13 / 8 mm
Drilling dia. in wood	40 / 25 mm
Chuck capacity	1.5 - 13 mm
Weight	2.2 kg

GSB 21-2 RE Professional**Impact Drill**

Technical data	
Part number	0 601 19C 600
Power input	1100 W
No-load speed	0 - 900/ 3000 rpm
Impact rate at no-load speed	0 - 15300 / 51000 bpm
Drilling dia. in concrete	22 / 13 mm
Drilling dia. in steel	16 / 8 mm
Drilling dia. in wood	40 / 25 mm
Chuck capacity	1.5 - 13 mm
Weight	2.9 kg

GSB 10 RE KIT Professional**Smart Kit**

Toolkit

Technical data	
Part number	0 601 216 1F4
Power input	500 W
No-load speed	2-2600 rpm
Impact rate	41600 ipm
Drilling dia. in concrete	10 mm
Drilling dia. in wood	20 mm
Drilling dia. in steel	8 mm
Weight	1.5 kg

GSB 13 RE KIT Professional**Smart Kit**

Toolkit

Technical data	
Part number	0 601 217 1F6
Power Input	600 W
No-load Speed	0-2800 rpm
Impact Rate	48000 ipm
Drilling dia. in Concrete	13 mm
Drilling dia. in wood	25 mm
Drilling dia. in steel	10 mm
Weight	1.6 kg

GBH 2-18 E Professional Rotary Hammer



Technical data	
Part number	0 611 258 2F0
Power input	550 W
Impact energy	0 - 1.7 J
Impact rate at rated speed	0 - 3960 bpm
Rated speed	450-1550 rpm
Drilling dia. concrete, hammer drill bits	4 - 18 mm
Max. drilling dia. steel	13 mm
Weight	2 kg

GBH 2-18 RE Professional Rotary Hammer



Technical data	
Part number	0 611 258 3F0
Power input	550 W
Impact energy	0 - 1.7 J
Impact rate at rated speed	0 - 3960 bpm
Rated speed	450-1550 rpm
Drilling dia. concrete, hammer drill bits	4 - 18 mm
Max. drilling dia. steel	13 mm
Weight	2 kg

GBH 2-20 RE Professional Rotary Hammer



Technical data	
Part number	0 611 25A 3K0/3F1
Power input	600 W
Impact energy	0 - 1.7 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1400 rpm
Drilling dia. concrete, hammer drill bits	4 - 20 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.3 kg

GBH 2-20 DRE Professional Rotary Hammer



Technical data	
Part number	0 611 25A 4F0/4F1
Power input	600 W
Impact energy	0 - 1.7 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1400 rpm
Drilling dia. concrete, hammer drill bits	4 - 20 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.3 kg

GBH 2-22 Professional Rotary Hammer



Technical data	
Part number	0 611 250 1K0
Impact energy	0 - 2.2 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1000 rpm
Drilling dia. concrete, hammer drill bits	4 - 22 mm
Max. drilling dia. masonry, core cutters	68 mm
Weight without cable	2.3 kg

GBH 2-22 E Professional Rotary Hammer



Technical data	
Part number	0 611 250 655
Power input	620 W
Impact energy	0 - 2.2 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1000 rpm
Drilling dia. concrete, hammer drill bits	4 - 22 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.3 kg

GBH 2-22 RE Professional Rotary Hammer



Technical data	
Part number	0 611 250 755
Power input	620 W
Impact energy	0 - 2.2 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1000 rpm
Drilling dia. concrete, hammer drill bits	4 - 22 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.3 kg

GBH 2-23 REA Professional Rotary Hammer



Technical data	
Part number	0 611 250 500
Power input	710 W
Impact energy	0 - 2.5 J
Impact rate at rated speed	0 - 4400 bpm
Rated speed	0 - 1000 rpm
Drilling dia. concrete, hammer drill bits	4 - 23 mm
Drilling dia. concrete, dust extraction unit	4 - 16 mm
Max. drilling dia. masonry, core cutters	68 mm
Weight	2.9 kg

GBH 2-26 E Professional Rotary Hammer



Technical data	
Part number	0 611 251 655
Power input	800 W
Impact energy	0 - 3 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Drilling dia. concrete, hammer drill bits	4 - 26 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.7 kg

GBH 2-26 RE Professional Rotary Hammer



Technical data	
Part number	0 611 251 755
Power input	800 W
Impact energy	0 - 3 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Drilling dia. concrete, hammer drill bits	4 - 26 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.7 kg

GBH 2-26 DRE Professional Rotary Hammer

Technical data	
Part number	0 611 253 755
Power input	800 W
Impact energy	0 - 3 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Drilling dia. concrete, hammer drill bits	4 - 26 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.7 kg

GBH 2-26 DFR Professional Rotary Hammer

Technical data	
Part number	0 611 254 76A
Power input	800 W
Impact energy	0 - 3 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Drilling dia. concrete, hammer drill bits	4 - 26 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.9 kg

GBH 2-28 D Professional Rotary Hammer**New!**

Technical data	
Part number	0 611 267 0K0
Power input	820 W
Impact energy	0 - 3.2 J
Impact rate at rated speed	0 - 5100 bpm
Rated speed	0 - 1300 rpm
Drilling dia. concrete, hammer drill bits	4 - 28 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.9 kg

GBH 2-28 DV Professional Rotary Hammer**New!**

Technical data	
Part number	0 611 267 100
Power input	820 W
Impact energy	0 - 3.2 J
Impact rate at rated speed	0 - 5100 bpm
Rated speed	0 - 1300 rpm
Drilling dia. concrete, hammer drill bits	4 - 28 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.9 kg

**GBH 2-28 DFV Professional Rotary Hammer****New!**

Technical data	
Part number	0 611 267 2K0
Power input	820 W
Impact energy	0 - 3.2 J
Impact rate at rated speed	0 - 5100 bpm
Rated speed	0 - 1300 rpm
Drilling dia. concrete, hammer drill bits	4 - 28 mm
Max. drilling dia. masonry, core cutters	68 mm
Max. drilling dia. steel	13 mm
Weight	2.9 kg

**GBH 3-28 DRE Professional Rotary Hammer**

Technical data	
Part number	0 611 23A 0K0
Power input	800 W
Impact energy	0 - 3.5 J
Impact rate at rated speed	0 - 4000 bpm
Rated speed	0 - 900 rpm
Drilling dia. concrete, hammer drill bits	4 - 28 mm
Max. drilling dia. masonry, core cutters	82 mm
Max. drilling dia. steel	13 mm
Weight	3.5 kg

**GBH 4-32 DFR Professional Rotary Hammer**

Technical data	
Part number	0 611 332 1F0
Power input	900 W
Impact energy	5 J
Impact rate at rated speed	0 - 3600 bpm
Rated speed	0 - 760 rpm
Drilling dia. concrete, hammer drill bits	32 mm
Max. drilling dia. masonry, core cutters	82 mm
Max. drilling dia. steel	13 mm
Weight	4.7 kg

**GBH 5-38 D Professional Rotary Hammer**

Technical data	
Part number	0 611 240 004
Power input	1050 W
Impact energy	7 / 9 J
Impact rate at rated speed	2900 bpm
Rated speed	320 rpm
Drilling dia. concrete, hammer drill bits	12 - 38 mm
Max. drilling dia. masonry, core cutters	40- 90 mm
Toolholder	SDS-max
Weight	5.8 kg

GBH 5-40 D Professional Rotary Hammer**New!**

Technical data	
Part Number	0 611 269 0K0
Power input	1100 W
Impact energy	8.5 J
Impact rate at rated speed	1500-2900 bpm
Rated speed	170 - 340 rpm
Drilling dia. concrete, hammer drill bits	12 - 40 mm
Max. drilling dia. masonry, core cutters	90 mm
Weight	6.8 kg

GBH 5-40 DCE Professional Rotary Hammer**New!**

Technical data	
Part Number	0 611 264 000
Power input	1150 W
Impact energy	2 - 11 J
Impact rate at rated speed	1500- 3050 bpm
Rated speed	170 - 340 rpm
Drilling dia. concrete, hammer drill bits	12 - 40 mm
Weight	6.8 kg



GBH 7-46 DE Professional Rotary Hammer



Technical data	
Part number	0 611 263 704
Power input	1350 W
Impact energy	2 - 15 J
Impact rate at rated speed	1375- 2800 bpm
Rated speed	145 - 280 rpm
Drilling dia. concrete, hammer drill bits	12 - 45 mm
Weight	8.2 kg

GBH 8-45 DV Professional Rotary Hammer

New!



Technical data	
Part number	0 611 265 0K0
Power input	1500 W
Impact energy	12.5 J
Impact rate at rated speed	1380-2760 bpm
Rated speed	150 - 305 rpm
Drilling dia. concrete, hammer drill bits	12 - 45 mm
Weight	8.9 kg

GBH 11 DE Professional Rotary Hammer



Technical data	
Part number	0 611 245 703
Power input	1500 W
Impact energy	5 - 18 J
Impact rate at rated speed	1100 - 2250 bpm
Rated speed	120 - 250 rpm
Drilling dia. concrete, hammer drill bits	12 - 52 mm
Weight	11.1 kg

GSH 5X Professional Demolition Hammer

New!



Technical data	
Part number	0 611 338 0K0
Power Input	1025 W
Impact rate	2750 bpm
Impact Energy	6.8 J
Toolholder	17mm Hex
Weight without cable	5.5 kg

GSH 5 Professional Demolition Hammer

New!



Technical data	
Part number	0 611 337 0K0
Power input	1100 W
Impact energy	7.5 J
Impact rate at rated speed	2850 rpm
Toolholder	SDS-max
Weight	5.6 kg

GSH 5 CE Professional Demolition Hammer

New!



Technical data	
Part number	0 611 321 000
Power Input	1150 W
Impact energy	2 - 13 J
Impact rate at rated speed	1300-2900 bpm
Toolholder	SDS-max
Weight	6.2 kg

GSH 11 VC Professional Demolition Hammer

New!



Technical data	
Part number	0 611 336 000
Power Input	1700 W
Impact rate	900-1700 bpm
Impact energy	23 J
Toolholder	SDS-max
Weight	11.4 kg

GSH 11 E Professional Demolition Hammer



Technical data	
Part number	0 611 316 755
Power input	1500 W
Impact energy	6 - 25 J
Impact rate at rated speed	900-1890 bpm
Toolholder	SDS-max
Weight	10.1 kg

GSH 16-30 Professional Demolition Hammer



Technical data	
Part number	0 611 335 100
Power input	1750 W
Impact energy	45 J
Impact rate at rated speed	1300 bpm
Toolholder	30 mm internal hexagon
Weight	16.5 kg

GSH 27 VC Professional Demolition Hammer



Technical data	
Part number	0 611 30A 000
Power input	2000 W
Impact energy	69 J
Impact rate at rated speed	1000 bpm
Toolholder	28 mm internal hexagon
Weight	29.5 kg

GVC 20 EX Professional Concrete Vibrator**New!**

Technical data	
Part number	0 601 283 0E0
Voltage	220 V
Power	1400 W
Electric frequency	50/60 Hz
Amperage	7.3 amps
Vibration frequency	20,000 vpm
Amplitude	4.3 mm
Capacity head	35 mm (dia.) x 288 mm comp
Flexible shaft	10 mm

GNF 35 CA Professional**Wall Chaser**

Technical data	
Part number	0 601 621 703
Power input	1400 W
No-load speed	9300 rpm
Adjustable groove depth	0 - 35 mm
Groove width	3 - 39 mm
Disc diameter	150 mm
Weight	4.1 kg

GBR 14 CA Professional**Wall Chaser**

Technical data	
Part number	0 601 773 703
Power input	1400 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Grinding head, diameter	125 mm
Weight	2.6 kg

GWS 6-100 Professional**Angle Grinder**

Technical data	
Part number	0 601 375 05D
Power input	670 W
No-load speed	11000 rpm
Grinding spindle thread	M 10
Disc diameter	100 mm
Wire cup brush, diameter	70 mm
Weight	1.8 kg

GWS 6-125 Professional**Angle Grinder**

Technical data	
Part number	0 601 375 15A
Power input	670 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	1.9 kg

GWS 7-100 Professional**Angle Grinder**

Technical data	
Part number	0 601 388 0F0
Power input	720 W
No-load speed	11000 rpm
Grinding spindle thread	M10
Disc diameter	100 mm
Rubber sanding plate, diameter	100 mm
Wire cup brush, diameter	70 mm
Weight	1.8 kg

GWS 7-125 Professional**Angle Grinder**

Technical data	
Part number	0 601 388 0F2
Power input	720 W
No-load speed	11000 rpm
Grinding spindle thread	M14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	1.9 kg

GWS 8-100 C Professional**Angle Grinder**

Technical data	
Part number	0 601 377 65A
Power input	850 W
No-load speed	11000 rpm
Grinding spindle thread	M 10
Disc diameter	100 mm
Rubber sanding plate, diameter	100 mm
Wire cup brush, diameter	70 mm
Weight	1.8 kg

GWS 850 CE Professional**Angle Grinder**

Technical data	
Part number	0 601 678 75A
Power input	850 W
No-load speed	2800-11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	1.9 kg

GWS 10-125 Professional**Angle Grinder**

Technical data	
Part number	0 601 821 2F0
Rated power input	1000 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight without cable	2.1 kg

GWS 11-125 CI Professional Angle Grinder



Technical data	
Part number	0 601 822 6F0
Power input	1100 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	2 kg

GWS 11-125 CIE Professional Angle Grinder



Technical data	
Part number	0 601 823 200
Power input	1100 W
No-load speed	2800-11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	2 kg

GWS 14-125 CI Professional Angle Grinder



Technical data	
Part number	0 601 824 2F0
Power input	1400 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	2.2 kg

GWS 15-125 CIH Professional Angle Grinder



Technical data	
Part number	0 601 824 2F0
Power input	1400 W
No-load speed	11000 rpm
Grinding spindle thread	M 14
Disc diameter	125 mm
Rubber sanding plate, diameter	125 mm
Wire cup brush, diameter	70 mm
Weight	2.2 kg

GPO 12 CE Professional Polisher



Technical data	
Part number	0 601 389 0F0
Power Input	1250 W
No-load speed	750 - 3000 rpm
Grinding spindle thread	M 14
Rubber sanding plate, diameter	180 mm
Weight	2.5 kg

GWS 20-180 Professional Heavy Duty Angle Grinder



Technical data	
Part number	0 601 849 155
Power input	2000 W
No-load speed	8500 rpm
Grinding spindle thread	M 14
Disc diameter	180 mm
Weight	5 kg

GWS 20-230 Professional Heavy Duty Angle Grinder



Technical data	
Part number	0 601 850 155
Power input	2000 W
No-load speed	6500 rpm
Grinding spindle thread	M 14
Disc diameter	230 mm
Weight	5.3 kg

GWS 22-180 Professional Heavy Duty Angle Grinder



Technical data	
Part number	0 601 881 AK0
Power input	2200 W
No-load speed	8500 rpm
Grinding spindle thread	M14
Disc diameter	180 mm
Weight	5 kg

GWS 22-230 Professional Heavy Duty Angle Grinder



Technical data	
Part number	0 601 882 AK0
Power input	2200 W
No-load speed	6500 rpm
Grinding spindle thread	M14
Disc diameter	230 mm
Weight	5.3 kg

GWS 24-180 Professional Heavy Duty Angle Grinder



Technical data	
Part number	0 601 853 455
Power input	2400 W
No-load speed	8500 rpm
Grinding spindle thread	M 14
Disc diameter	180 mm
Weight	4.9 kg

GWS 24-180 LVI Professional Heavy Duty Angle Grinder**New!**

Technical data	
Part number	0 601 892 F00
Power input	2400 W
No-load speed	8500 rpm
Grinding spindle thread	M 14
Disc diameter	180 mm
Main handle	Bow (rotatable)
Weight	4.9 kg

GWS 26-180 H Professional Heavy Duty Angle Grinder

Technical data	
Part number	0 601 855 100
Power input	2400 W
No-load speed	8500 rpm
Grinding spindle thread	M 14
Disc diameter	180 mm
Weight	6 kg

GWS 24-230 Professional Heavy Duty Angle Grinder

Technical data	
Part number	0 601 854 455
Power input	2400 W
No-load speed	6500 rpm
Grinding spindle thread	M 14
Disc diameter	230 mm
Weight	6 kg

GWS 26-230 H Professional Heavy Duty Angle Grinder

Technical data	
Part number	0 601 855 100
Power input	2400 W
No-load speed	6500 rpm
Grinding spindle thread	M 14
Disc diameter	230 mm
Weight	6 kg

GGG 3000 L Professional Straight Grinder**New!**

Technical data	
Part number	0 601 224 0F0
Input power	300 W
No-load speed	0 - 28000 rpm
Toolholder (Collet upto)	8 mm diameter
Spindle collar diameter	41 mm
Weight	1.5 kg

GGG 5000 L Professional Straight Grinder**New!**

Technical data	
Part number	0 601 224 1F0
Power input	500 W
No-load speed	33000 rpm
Spindle collar diameter	41 mm
Weight	1.4 kg

GGG 28 LCE Professional Straight Grinder**New!**

Technical data	
Part number	0 601 221 100
Power input	650 W
No-load speed	10000 - 28000 rpm
Spindle collar diameter	43 mm
Weight	1.6 kg

GNA 2.0 Professional Nibbler

Technical data	
Part number	0 601 530 103
Power input	500 W
Cutting track width	6 mm
Pre-drilling for interior cutout	16 mm
Smallest radius	3 mm
Cutting capacity Steel (400 N/mm ²), max.	2.0 mm
Cutting capacity Steel (600 N/mm ²), max.	1.4 mm
Cutting capacity Steel (800 N/mm ²), max.	1.0 mm
Weight	2 kg

GNA 3.5 Professional Nibbler

Technical data	
Part number	0 601 533 103
Power input	620 W
Cutting track width	6 mm
Pre-drilling for interior cutout	41 mm
Smallest radius	70 mm
Cutting capacity Steel (400 N/mm ²), max.	3.5 mm
Cutting capacity Steel (600 N/mm ²), max.	2.4 mm
Cutting capacity Steel (800 N/mm ²), max.	1.6 mm
Weight	3.5 kg



GSC 2.8 Professional

Shear



Technical data	
Part number	0 601 506 103
Power input	500 W
Stroke rate, load	1500 spm
Stroke rate at no load	2400 spm
Cutting capacity Steel (400 N/mm ²), max.	2.8 mm
Cutting capacity Steel (600 N/mm ²), max.	2.2 mm
Cutting capacity Steel (800 N/mm ²), max.	1.9 mm
Cutting capacity Aluminium (250 N/mm ²), max.	3.5 mm
Weight	2.7 kg

GSC 160 Professional

Shear



Technical data	
Part number	0 601 500 403
Power input	500 W
Stroke rate, load	3500 spm
Stroke rate at no load	5000 spm
Cutting capacity Steel (400 N/mm ²), max.	1.6 mm
Cutting capacity Steel (600 N/mm ²), max.	1.2 mm
Cutting capacity Steel (800 N/mm ²), max.	0.7 mm
Cutting capacity Aluminium (250 N/mm ²), max.	2.2 mm
Weight	1.8 kg

GDB 2500 WE Professional Diamond Concrete Cutter



Technical data	
Part number	0 601 18P 703
Power input	2500 W
Rated speed	410 / 900 rpm
Concrete, optimum range	82 - 132 mm
Concrete, possible range	32 - 212 mm
Toolholder	R 1/2", 1 1/4"
Suitability	Wet drilling in concrete
Weight	11.8 kg

S 500 A Professional

Drill Stand



Technical data	
Part number	0 601 190 025
Drill stroke	500 mm
Length	1000 mm
Weight	12.5 kg

GST 65 E Professional

Jigsaw



Technical data	
Part number	0 601 509 2F1/2K0
Power input	400 W
No-load stroke rate	500-3100 spm
Cable length	2.5 m
Stroke height	18 mm
Cutting depth in wood	65 mm
Cutting depth in aluminium	12 mm
Cutting depth in non-alloyed steel	3 mm
Weight	1.7 kg

GST 85 PBE Professional

Jigsaw



Technical data	
Part number	0 601 587 65B
Power input	580 W
No-load stroke rate	500-3100 spm
Stroke height	26 mm
Cutting depth in wood	85 mm
Cutting depth in aluminium	20 mm
Cutting depth in non-alloyed steel	10 mm
Weight	2.4 kg

GST 8000 E Professional

Jigsaw



Technical data	
Part number	0 601 58H 0F0
Power input	710 W
No-load stroke rate	500-3100 spm
Stroke height	20 mm
Cutting depth in wood	80 mm
Cutting depth in aluminium	20 mm
Cutting depth in non-alloyed steel	10 mm
Weight	2.5 kg

GST 25 M Professional

Jigsaw



Technical data	
Part number	0 601 516 0K0
Power input	670 W
No-load stroke rate	500-2600 spm
Stroke height	24 mm
Cutting depth in wood	80 mm
Cutting depth in aluminium	25 mm
Cutting depth in non-alloyed steel	15 mm
Weight	2.7 kg

GST 150 BCE Professional

Jigsaw



Technical data	
Part number	0 601 513 0F0
Power input	780 W
No-load stroke rate	500-3100 spm
Cable length	4 m
Stroke height	26 mm
Cutting depth in wood	150 mm
Cutting depth in aluminium	20 mm
Cutting depth in non-alloyed steel	10 mm
Weight	2.7 kg



GCO 2000 Professional**Cut-Off Saw**

Technical data	
Part number	0 601 B17 0F0
Power input	2000 W
Cutting capacity, rectangle	85 x 180 mm
Cutting capacity, square	120 x 120 mm
Cutting capacity, L-profile	138 x 138 mm
No-load speed	3500 rpm
Grinding disc diameter	355 mm
Grinding bore diameter	25.4 mm
Weight	17 kg

GCO 2400 J Professional**Cut-Off Saw**

Technical data	
Part number	0 601 B18 0K0
Power input	2400 W
Cutting capacity, rectangle	85 x 180 mm
Cutting capacity, square	110 x 110 mm
Cutting capacity, L-profile	130 x 130 mm
No-load speed	3800 rpm
Grinding disc diameter	355 mm
Grinding bore diameter	25.4 mm
Weight	17 kg

GCO 2 Professional**Cut-Off Saw**

Technical data	
Part number	0 601 B17 3F0
Power input	2000 W
Cutting capacity, rectangle	185 x 85 mm
Cutting capacity, square	110 x 110 mm
Cutting capacity, L-profile	130 x 130 mm
No-load speed	3500 rpm
Grinding disc diameter	355 mm
Grinding bore diameter	25.4 mm
Weight	14.6 kg

GCD 12 JL Professional**Mitre Saw**

Technical data	
Part number	0 601 B28 0F0
Power input	2000 W
No-load speed	1500 rpm
Laser type	650 nm
Laser class	1 M
Weight	20 kg

GCM 12 GDL Professional**Mitre Saw**

Technical data	
Part number	0 601 B23 6K0
Power input	1800 W
Cutting capacity, 0°	103 x 341 mm
Cutting capacity, 45° mitre	104 x 240 mm
Cutting capacity, 45° incline	51 x 341 mm
Mitre setting	52° L / 60° R
Incline setting	47° L / 47° R
No-load speed	3800 rpm
Saw blade diameter	305 mm
Saw blade bore	30 mm
Weight without cable	32.1 kg

GCM 10 M Professional**Mitre Saw**

Technical data	
Part number	0 601 B20 1K0
Power input	2000 W
Cutting capacity, 0°	89 x 89 mm
Cutting capacity, 45° mitre	89 x 59 mm
Cutting capacity, 45° incline	58 x 85 mm
Mitre setting	47° L / 47° R
No-load speed	4500 rpm
Saw blade diameter	254 mm
Saw blade bore	25.4 mm
Weight	13.8 kg

GCM 12 MX Professional**Mitre Saw**

Technical data	
Part number	0 601 B21 1K0
Power input	1800 W
Cutting capacity, 0°	100 x 150 mm
Cutting capacity, 45° mitre	100 x 100 mm
Cutting capacity, 45° incline	38 x 141 mm
Mitre setting	52° L / 52° R
Incline setting	47° L / 2° R
No-load speed	4300 rpm
Weight without cable	20.7 kg

GKS 190 Professional**Circular Saw**

Technical data	
Part number	0 601 623 0F1
Power input	1400 W
No-load speed	5500 rpm
Saw blade bore	20 mm
Saw blade diameter	184 mm
Cutting depth (90°)	67 mm
Cutting depth (45°)	48 mm
Weight	4.1 kg

GKS 235 Professional**Circular Saw**

Technical data	
Part number	0 601 57A 0F2
Power input	2100 W
No-load speed	5000 rpm
Saw blade bore	25 mm
Saw blade diameter	235 mm
Cutting depth (90°)	85 mm
Cutting depth (45°)	65 mm
Weight	7.6 kg

GKS 7000 Professional**Circular Saw**

Technical data	
Part number	0 601 676 0K1
Power input	1100 W
No-load speed	5200 rpm
Saw blade bore	19 mm
Saw blade diameter	184 mm
Cutting depth (90°)	65 mm
Cutting depth (45°)	47 mm
Weight	3.6 kg

GSA 1300 PE Professional

Sabre Saw

New!



Technical data	
Part number	0 601 64E 2K0
Power input	1300 W
No-load stroke rate	0 - 2900 spm
Saw, stroke length	28 mm
Cutting depth in wood	250 mm
Cutting depth in metal profiles and metal pipes	20 mm
Weight	4.1 kg



GSA 1100 E Professional

Sabre Saw



Technical data	
Part number	0 601 64C 8K0
Power input	1100 W
No-load stroke rate	0 - 2700 spm
Saw, stroke length	28 mm
Cutting depth in wood	230 mm
Cutting depth in metal profiles and metal pipes	20 mm
Weight	3.6 kg

GKE 35 BCE Professional

Chainsaw



Technical data	
Part number	0 601 597 603
Power input	2100 W
Chain bar, length	400 mm
Chain pitch	3/8 "
Chain speed	12.00 m/s
Cable length	2.5 m
Chain gauge	1.3 mm
Brake time of kick-back brake	<= 0,1 s
Brake time of run-out brake	<= 1 s
Weight	4.6 kg

GKE 40 BCE Professional

Chainsaw



Technical data	
Part number	0 601 597 703
Power input	2100 W
Chain bar, length	350 mm
Chain pitch	3/8 "
Chain speed	12.00 m/s
Cable length	2.5 m
Chain gauge	1.3 mm
Brake time of kick-back brake	<= 0,1 s
Brake time of run-out brake	<= 1 s
Weight	4.8 kg

GTS 10 Professional

Table Saw



Technical data	
Part number	0 601 B30 200
Saw blade diameter	254 mm
D x L x H	73x78x34 cm
No-load speed	3650 rpm
Weight	34 kg

GEX 150 AC Professional

Sander



Technical data	
Part number	0 601 372 768
Power input	340 W
Sanding plate diameter	150 mm
No-load speed	4500-12000 rpm
Orbital stroke rate	9000-24000 opm
Eccentricity	2.00 mm
Sanding sheet / disc attachment	Velcro-type fastening
Oscillating circuit diameter	4 mm
Weight	2.1 kg

GEX 125-1 AE Professional Random Orbit Sander



Technical data	
Part number	0 601 387 5K0
Power input	250 W
Sanding plate diameter	125 mm
No-load speed	7500-12000 rpm
Orbital stroke rate	15000-24000 opm
Eccentricity	1.25 mm
Sanding sheet / disc attachment	Velcro-type fastening
Oscillating circuit diameter	2.5 mm
Weight	1.3 kg

GEX 150 AVE Professional Random Orbit Sander

New!



Technical data	
Part number	0 601 37B 1K0
Power input	400 W
Sanding plate diameter	150 mm
No-load speed	5500-12000 rpm
Sanding sheet / disc attachment	Velcro-type fastening
Oscillating circuit diameter	4 mm
Weight	2.5 kg

GSS 23 AE Professional

Orbital Sander



Technical data	
Part number	0 601 070 700
Power input	190 W
No-load speed	7000-12000 rpm
No-load orbital stroke rate	14000-24000 opm
Oscillating circuit diameter	2.0 mm
Sanding plate, width	92 mm
Sanding plate, length	182 mm
Sanding sheet for clamping, width	93 mm
Sanding sheet for clamping, length	230 mm
Weight	1.7 kg

GOP 250 CE Professional

Multi-cutter



Technical data	
Part number	0 601 230 0K0
Power input	250 W
Oscillation angle on left/right	1.4°
Weight	1.5 kg

GMR 1 Professional**Router****New!**

Technical data	
Part number	0 601 60A 0K0
Rated power input	550 W
No-load speed	33000 rpm
Toolholder	6 mm
Weight without cable	1.5 kg

POF 1400 ACE Professional**Router****Technical data**

Part number	0 603 26C 800
Power input	1300 W
R.P.M.	11000-28000
Plunge depth	55 mm
Plunge presets	5 mm
Collect size	8 mm
Weight	3 kg

**GOF 1600 CE Professional****Router**

Technical data	
Part number	0 601 624 0F0
Power input	1600 W
No-load speed	10000 - 25000 rpm
Stroke	76 mm
Weight	5.8 kg

GHO 10-82 Professional**Planer****Technical data**

Part number	0 601 594 007/060
Power input	710 W
Adjustable chip thickness	0 - 1.0 mm
Adjustable rebating depth	0 - 9 mm
No-load speed	16500 rpm
Weight	2.5 kg

**GHO 26-82 Professional****Planer**

Technical data	
Part number	0 601 594 103/160
Power input	710 W
Adjustable chip thickness	0 - 2.6 mm
Adjustable rebating depth	0 - 9 mm
No-load speed	16500 rpm
Weight	2.6 kg

GBG 6 Professional**Bench Grinder****New!****Technical data**

Part number	0 601 27A 0F0
Power input	350 W
Grinding disc diameter	150 mm
Grinding disc widths	20 mm
Grinding disc bore	20 mm
Weight	10 kg

GBG 8 Professional**Bench Grinder**

Technical data	
Part number	0 601 27A 1F0
Power input	600 W
Grinding disc diameter	200 mm
Grinding disc widths	25 mm
Grinding disc bore	32 mm
Weight	16.5 kg

GAS 11-21 Professional**Dust Extractor****Technical data**

Part number	0 601 97A 004
Power input	900 W
Container volume, gross	21 l
Max. airflow	50 l/sec
Max. ventilating pressure	150 mbar
Weight	6.30 kg

GAS 20 L Professional**Dust Extractor****New!**

Technical data	
Part number	0 601 97B 000
Rated power input	1200 W
Container volume, gross	19 l
Container volume net water	20 l
Max. airflow	62 l/sec
Max. ventilating pressure	215 mbar
Weight without cable	6.4 kg

GAS 35 SFC Professional**Dust Extractor****New!****Technical data**

Part number	0 601 9C3 060
Rated power input	1380 W
Container volume, gross	35 l
Container volume net water	19.2 l
Max. airflow	74 l/sec
Max. ventilating pressure	254 mbar
Weight without cable	11.6 kg

GAS 50 Professional**Dust Extractor**

Technical data	
Part number	0 601 989 103
Power input	1200 W
Container volume, gross	50 l
Container volume net water	43 l
Container volume net dust	45 l
Dust bag volume, net	21 l
Filter surface	8600 cm ²
Max. airflow	61 l/sec
Max. ventilating pressure	248 mbar
Weight	16 kg

GAS 55 M AFC Professional**Dust Extractor****New!****Technical data**

Part number	0 601 9C3 360
Rated power input	1380 W
Container volume, gross	55 l
Container volume net water	40 l
Max. airflow	74 l/sec
Max. ventilating pressure	254 mbar
Weight without cable	16.2 kg

GBL 800E Professional Blower

Technical data	
Part number	0 601 980 4F0
Power input	800 W
No-load speed	16000 rpm
Volumetric flow rate	4.5 m³/min
Weight	1.8 kg



GHG 500-2 Professional Heat Gun

Technical data	
Part number	0 601 94A 050
Power input	1600 W
Length	255 mm
Height	255 mm
Working temperature	300 - 500 °C
Airflow	240-450 l/min
Infinitely variable temperature control	x
Control, airflow	2-stage
Weight	0.8 kg



GHG 600-3 Professional Heat Gun

Technical data	
Part number	0 601 94B 004
Power input	1800 W
Length	255 mm
Height	255 mm
Working temperature	50 - 600 °C
Infinitely variable temperature control	x
Control, airflow	3-step
Weight	0.8 kg



GHG 600 CE Professional Heat Gun

Technical data	
Part number	0 601 94C 704
Power input	2000 W
Temperature range	1000 - 6000
Airflow rate	350-550 l/min.
Weight	0.9 kg



GHG 630 DCE Professional Heat Gun

Technical data	
Part number	0 601 94C 704
Rated power input	2000 W
Working temperature	50 - 630 °C
Airflow	150 - 500 l/min
Infinitely variable temperature control	x
Control, airflow	infinitely variable
Weight	0.9 kg



GDM 13-34 Professional Marble Cutter

Technical data	
Part number	0 601 36A 2K0
Power Input	1300 W
No-load speed	12000 rpm
Saw blade diameter	110 mm
Saw blade bore	20.0 mm
Cutting depth (90°)	34 mm
Cutting depth (45°)	22 mm
Weight	2.8 kg



GDC 34 M Professional Marble Cutter

Technical data	
Part number	F 002 G30 104
Power input	1300 W
No-load speed	12000 rpm
Saw blade diameter	110 mm
Saw blade bore	20.0 mm
Cutting depth (90°)	34 mm
Cutting depth (45°)	22 mm
Weight	3.3 kg



IXO 3 Professional Cordless Screwdriver

Technical data	
Part number	0 601 960 2K0
Voltage	3.6 V
Torque, max. (hard screwdriving applications)	4 Nm
No-load speed	0 - 180 rpm
Max. screw diameter	5 mm
Weight	0.3 kg



GSR ProDrive Professional Cordless Screwdriver

Technical data	
Part number	0 601 9A2 0K1
Voltage	3.6 V
Torque, max. (hard screwdriving applications)	7 Nm
No-load speed	0 - 250 rpm
Max. screw diameter	5 mm
Weight	0.5 kg



GSR 10.8-2 Li Professional Cordless Drill/Driver

Technical data	
Part number	0 601 868 1K0
Voltage	10.8 V
Torque, max. (hard screwdriving applications)	30 Nm
No-load speed (1 st gear/ 2 nd gear)	0 - 350/1300 rpm
Max. screw diameter	7 mm
Max. drilling diameter in wood	19 mm
Max. drilling diameter in steel	10 mm
Torque settings	20
Weight	0.95 kg
Battery	2 x 1.3 Ah



GSR 10.8 Li Professional Cordless Screwdriver


Technical data	
Part number	0 601 992 9F0
Voltage	10.8 V
Torque, max. (hard screwdriving applications)	30 Nm
No-load speed (1 st gear/ 2 nd gear)	0 - 350/1300 rpm
Max. screw diameter	7 mm
Max. drilling diameter in wood	19 mm
Max. drilling diameter in steel	10 mm
Torque settings	20
Weight	0.8 kg
Battery	2 x 1.3 Ah

GWI 10.8 V-Li Professional Cordless Angle Driver


Technical data	
Part number	0 601 360 U06
No-load speed	0 - 585 rpm
Max. screw diameter	5 mm
Max. drilling diameter in wood	10 mm
Max. drilling diameter in steel	8 mm
Toolholder 1/4"	internal hexagon
Weight	1.1 kg
Battery	1 x 1.3 Ah

GSR 1080 Li Professional Cordless Drill/Driver
New!


Technical data	
Part number	0 601 9A8 9K0
Voltage	10.8 V
Torque, max. (hard screwdriving applications)	27 Nm
No-load speed (1 st gear/ 2 nd gear)	0 - 400/1200 rpm
Max. screw diameter	6 mm
Max. drilling diameter in wood	23 mm
Max. drilling diameter in steel	10 mm
Torque settings	25+1
Chuck clamping range	1 - 10 mm
Weight	1.25 kg
Battery	2 x 1.3 Ah

GSR 1440 Li Professional Cordless Drill/Driver
New!


Technical data	
Part number	0 601 9A8 4K0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	30 Nm
No-load speed (1 st gear/ 2 nd gear)	0-420/1400 rpm
Max. screw diameter	7 mm
Max. drilling diameter in wood	25 mm
Max. drilling diameter in steel	10 mm
Torque settings	25+1
Chuck clamping range	1 - 10 mm
Weight	1.3 kg
Battery	2 x 1.3 Ah

GSR 14.4 V-Li Professional Cordless Drill/Driver
New!


Technical data	
Part number	0 601 866 0B0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	60 Nm
No-load speed (1 st gear/ 2 nd gear)	0 - 500/1600 rpm
Max. screw diameter	7 mm
Max. drilling diameter in wood	32 mm
Max. drilling diameter in steel	13 mm
Torque settings	18+1
Chuck clamping range	1.5 - 13 mm
Weight	1.7 kg
Battery	2 x 2.6 Ah

GSR 1800 Li Professional Cordless Drill/Driver
New!


Technical data	
Part number	0 601 9A8 3K0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	34 / 15 Nm
No-load speed (1 st gear/ 2 nd gear)	0- 400/1300 rpm
Max. screw diameter	8 mm
Max. drilling diameter in wood	29 mm
Max. drilling diameter in steel	10 mm
Torque settings	25+1
Weight	1.4 kg
Battery	1.5 Ah

GDR 10.8 V-Li Professional Cordless Impact Driver


Technical data	
Part number	0 601 9A6 9F0
Battery voltage	10.8 V
No-load speed(1 st /2 nd gear)	0 - 2600 rpm
Tightening torque max.	105 Nm
HEX bit holder size	6.35 mm/1/4 inch
Charging time (with AL1130CV)	30 min
Impact rate	0 - 3100 bpm
Capacity for standard bolting	M4 - M12
LED light	3-ringed LED
Brake function	Yes
Weight including battery	0.96 kg
Battery	2 x 1.3 Ah

GDR 14.4 V-Li Professional Cordless Impact Driver


Technical data	
Part number	0 601 9A1 4K0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	150 Nm
No-load speed	0 - 2800 rpm
Rated impact rate	0 - 3200 bpm
Screw diameter	M 6 - M 14
Toolholder	1/4" internal hexagon
Weight	1.6 kg
Battery	2 x 2.6 Ah

GDR 18 V-Li Professional Cordless Impact Driver


Technical data	
Part number	0 601 9A1 3K0
Voltage	18 V
Torque, max. (hard screwdriving applications)	160 Nm
No-load speed	0 - 2800 rpm
Rated impact rate	0 - 3200 bpm
Screw diameter	M 6 - M 14
Toolholder	1/4" internal hexagon
Weight	1.7 kg
Battery	2 x 2.6 Ah

GDR 1080 Li Professional Cordless Impact Driver


Technical data	
Part number	0 601 9B3 9K0
Voltage	10.8 V
Torque, max. (hard screwdriving applications)	110 Nm
No-load speed	0 - 2600 rpm
Rated impact rate	0 - 3200 bpm
Screw diameter	M4 - M12
Toolholder	1/4" internal hexagon
Weight	1.1 kg
Battery	2 x 1.3 Ah

GDR 1440 Li Professional Cordless Impact Driver
New!


Technical data	
Part number	0 601 9B3 4K0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	130 Nm
No-load speed	0 - 2900 rpm
Rated impact rate	0 - 3300 bpm
Screw diameter	M4 - M14
Toolholder	1/4" internal hexagon
Weight	1.2 kg
Battery	2 x 1.3 Ah

GBH 36 V-Li Professional Cordless Rotary Hammer


Technical data	
Part number	0 611 900 R0F
Voltage	36 V
Rated power input	600 W
Impact energy	0 - 3 J
Rated speed	0 - 960 rpm
Impact rate at rated speed	0 - 4260 bpm
Drilling dia. concrete, hammer drill bits	4 - 26 mm
Max. drilling dia. in wood	30 mm
Max. drilling dia. in steel	13 mm
Weight	4.3 kg
Battery	1 x 2.6 Ah

GDS 14.4 V-Li Professional Cordless Impact Wrench


Technical data	
Part number	0 601 9A1 TF0
Voltage	14.4 V
Torque, max. (hard screwdriving applications)	170 Nm
No-load speed	0 - 2800 rpm
Rated impact rate	0 - 3200 bpm
Screw diameter	M 6 - M 16
Toolholder	1/2" external square
Weight	1.6 kg
Battery	2 x 2.6 Ah

GDS 18 V-Li Professional Cordless Impact Wrench


Technical data	
Part number	0 601 9A1 SF0/SF1
Voltage	18 V
Torque, max. (hard screwdriving applications)	180 Nm
No-load speed	0 - 2800 rpm
Rated impact rate	0 - 3200 bpm
Screw diameter	M 6 - M 16
Toolholder	1/2" external square
Weight	1.7 kg
Battery	2 x 2.6 Ah

GDS 18 V-Li HT Professional Cordless Impact Wrench
New!


Technical data	
Part number	0 601 9A1 3F1
Voltage	18 V
Torque, max. (hard screwdriving applications)	650 Nm
No-load speed	0 - 1900 rpm
Rated impact rate	0 - 2100 bpm
Screw diameter	M 12 - M 20
Toolholder	1/2" external square
Weight	3 kg
Battery	2 x 3 Ah

GSA 10.8 V-Li Professional Cordless Sabre Saw


Technical data	
Part number	060 164L 9K0
Battery voltage	10.8 V
No-load speed (1 st gear/2 nd gear)	0 - 3000
Stroke lengths	14.5 mm
Weight	1.2 kg
Battery	2 x 2.6 Ah

GSB 10.8-2-Li Professional Cordless Impact Drill


Technical data	
Part number	0 601 9B6 9K0
Torque, max. (hard screwdriving applications)	30 Nm
No-load speed (1 st gear/2 nd gear)	0 - 380/1300 rpm
Max. screw diameter	7 mm
Max. drilling dia. in wood	19 mm
Max. drilling dia. in steel	10 mm
Torque settings	20
Chuck clamping range	10 mm
Weight	1 kg
Battery	1 x 1.3 Ah

GAS 18 V-Li Professional Cordless All Purpose Extractor


Technical data	
Part number	2 607 336 607
Battery voltage	18 V
Container volume, gross	1 l
Max. airflow	19.3 l/sec
Max. ventilating pressure	40 mbar
Weight without cable	1.4 kg

GSB 14.4 V-Li Professional Cordless Impact Drill

Technical data	
Part number	0 601 9B6 9K0
Battery voltage	14.4 V
Battery capacity	2.6 Ah
No-load speed	0-500/1400rpm
Drilling dia. in wood	25 mm
Drilling dia. in steel	10 mm
Drilling dia. in brick	10 mm
Torque range (hard/soft)	38/16 Nm
Clutch setting	25+drilling
No. of batteries	2 x 2.6 Ah, Li-Ion
Weight	1.6 kg

GSB 18 VE-2 Li Professional Cordless Impact Drill**New!**

Technical data	
Part number	0 601 862 3B0
Voltage	18 V
Torque, max.	85 Nm
No-load speed (1 st gear / 2 nd gear)	0-420/1800 rpm
Max. impact rate	27000 bpm
Max. drilling dia. in wood	45 mm
Max. drilling dia. in masonry	16 mm
Torque settings	25+1
Chuck clamping range	1.5 - 13 mm
Weight	2.2 kg

GWS 18 V-Li Professional Cordless Angle Grinder

Technical data	
Part number	0 601 93A 302
Voltage	18 V
No-load speed	10000 rpm
Roughing/cutting disc, diameter	115 mm
Battery	2 x 3 Ah

GOP 10.8 V-Li Professional Cordless Multicutter

Technical data	
Part number	0 601 858 006
Battery voltage	10.8 V
Battery capacity	1.3 Ah No-load speed
speed	5000-20000 rpm
Oscillation angle on left/right	1.4°
Weight	1 kg

GSR 7.2-2 Professional Cordless Drill / Driver

Technical data	
Part number	0 601 918 NF2
Voltage	7.2 V
Torque, max.	21 Nm
No-load speed (1 st gear / 2 nd gear)	0-400/1000 rpm
Max. screw diameter	6 mm
Torque settings	25+1
Chuck clamping range	1 - 10 mm
Battery	2 x 2 Ah, Ni-cd
Weight	1.4 kg

GSR 9.6-2 Professional Cordless Drill / Driver

Technical data	
Part number	0 601 918 LK0
Voltage	9.6 V
Torque, max.	25 Nm
No-load speed (1 st gear / 2 nd gear)	0-400/1000 rpm
Max. screw diameter	6 mm
Chuck clamping range	1 - 10 mm
Weight	1.5 kg
Battery	2 x 1.5 Ah, Ni-cd

GSR 12-2 Professional Cordless Drill / Driver

Technical data	
Part number	0 601 918 JF1
Voltage	12 V
Torque, max.	27 Nm
No-load speed (1 st gear / 2 nd gear)	0-400/1200 rpm
Max. screw diameter	7 mm
Torque settings	25+1
Chuck clamping range	1 - 10 mm
Weight	1.6 kg
Battery	2 x 1.5 Ni-cd

GSR 14.4-2 Professional Cordless Drill / Driver

Technical data	
Part number	0 601 918 GK0
Voltage	14.4 V
Torque, max.	25 Nm
No-load speed (1 st gear / 2 nd gear)	0-400/1400 rpm
Max. screw diameter	8 mm
Chuck clamping range	1 - 10 mm
Weight	1.7 kg
Battery	2 x 1.5 Ni-cd

GSR 18-2 Professional Cordless Drill / Driver

Technical data	
Part number	0 601 918 3F0
Voltage	18 V
Torque, max.	45 Nm
No-load speed (1 st gear / 2 nd gear)	0-400/1250 rpm
Max. screw diameter	8 mm
Max. drilling dia. in wood	29 mm
Max. drilling dia. in steel	10 mm
Torque settings	25+1
Chuck clamping range	1.5 - 10 mm
Battery	2 x 1.5 Ni-cd
Weight	1.9 kg

GSB 12-2 Professional Cordless Impact Drill

Technical data	
Part number	0 611 9A7 5K0
Voltage	12 V
Torque, max.	30 Nm
No-load speed (1 st gear / 2 nd gear)	0-450/1250rpm
Max. impact rate	18750 bpm
Weight incl. battery	1.6 kg
Torque settings	22+1
Max. drilling dia. in wood	25 mm
Max. drilling dia. in steel	10 mm
Max. drilling dia. in masonry	8 mm
Torque settings	22+1
Chuck clamping range	1.5 - 10 mm
Weight	1.6 kg
Battery	2 x 1.5 Ni-cd

GSB 14.4-2 Professional Cordless Impact Drills



Technical data	
Part number	0 601 9A7 4K0
Voltage	14.4 V
Torque, max.	36 Nm
No-load speed (1 st gear/2 nd gear)	0-550/1550 rpm
Max. impact rate	23250 bpm
Max. drilling dia. in wood	25 mm
Max. drilling dia. in steel	10 mm
Max. drilling dia. in masonry	10 mm
Torque settings	22+1
Chuck clamping range	1.5 - 10 mm
Battery	2 x 1.5 Ni-cd
Weight	1.7 kg

GMS 100 M Professional

Detector



Technical data	
Part number	0 601 081 100
Detectable materials	Metal objects, live wires
Max. measurement depth	100 mm
Power supply	1 x 9 V 6LR61
Weight	0.26 kg

GMS 120 Professional

Detector



Technical data	
Part number	0 601 081 000
Detectable materials	Electrical cables, metals, wooden substructures
Max. measurement depth	120 mm
Automatic deactivation facility, approx.	5 min
Power supply	1 x 9 V 6LR61
Weight	0.27 kg

D-tect 150 CNT Professional

Detector



Technical data	
Part number	0 601 010 055
Detectable materials	Plastic pipes, ferrous metals, non-ferrous metals, wooden substructures, live cables
Max. measurement depth	150 mm
Accuracy	± 5 mm
Automatic deactivation facility, approx.	5 min
Power supply	4 x 1.5V LR6 (AA)
Weight	0.7 kg

GPL 5 Professional

Point Laser



Technical data	
Part number	0 601 066 200
Working range	30 m
Levelling accuracy	0.3 mm/m
Tripod connection	1/4"
Dust and splash protection	IP 5X
Weight	0.25 kg

GLL 2 Professional

Line Laser



Technical data	
Part number	0 601 063 700
Working range	10 m
Levelling accuracy	0.3 mm/m
Self-levelling range	± 4°
Laser class	2
Dust and splash protection	IP 5X
Power supply	3 x 1.5V LR6 (AA)
Weight	0.25 kg

GCL 25 (standalone) Professional

Line Laser



Technical data	
Part number	0 601 066 B00
Working range	10 m
Levelling accuracy	0.3 mm/m
Self-levelling range	± 4°
Laser class	2
Tripod connection	1/4" & 5/8"
Power supply	4 x AA LR06 1.5 V
Weight	1.5 kg

GLL 2X Professional

Line Laser



Technical data	
Part number	0 601 063 A80
Working range	5 m
Levelling accuracy	±0.5 mm/m
Self-levelling range	±4°
Laser class	2
Power supply	2 x 1.5-V-LR03 (AAA)
Weight	0.25 kg

GLL 3X Professional

Line Laser



Technical data	
Part number	0 601 063 CJD
Working range	15 m
Levelling accuracy	±0.5 mm/m
Self-levelling range	±4°
Tripod connection	1/4"
Power supply	4 x 1.5 V (LR6) AA

GLL 2-50 Professional

Line Laser



Technical data	
Part number	0 601 063 100
Working range	20 m
Levelling accuracy	3 mm/m
Self-levelling range	±4°
Laser class	2
Tripod connection	1/4"
Power supply	3 x 1.5 V (AA)
Weight	0.45 kg

GLL 2-80 P Professional**Line Laser**

Technical data	
Part number	0 601 063 205
Working range	20 m
Levelling accuracy	0.2 mm/m
Self-levelling range	±4°
Laser class	2
Tripod connection	IP54
Dust and splash protection	1/4", 5/8"
Power supply	4 x 1.5 V (AA)
Weight	0.68 kg

GLL 3-80 P Professional**Line Laser**

Technical data	
Part number	0 601 063 300
Working range	20 m
Levelling accuracy	0.2 mm/m
Self-levelling range	±4°
Laser class	2
Tripod connection	IP54
Dust and splash protection	1/4", 5/8"
Power supply	4 x 1.5 V LR6 (AA)
Weight	0.76 kg

GRL 300 HV Set Professional**Rotation Laser**

Technical data	
Part number	0 601 061 503
Working range	300 m
Levelling accuracy	0.1 mm/m
Self-levelling range	± 5° (8%)
Laser class	3R
Dust and splash protection	IP54
Power supply	2 x 1.2 VHR20 (D)(9 Ah)
Weight	1.8 kg

GTL 3 Professional**Line Laser**

Technical data	
Part number	0 601 015 200
Working range	20 m
Levelling accuracy	±0.2 mm/m
Laser class	635 nm/< 1 mW/2
Dust and splash protection	IP54
Power supply	2 x 1.5 V LR20 (D)
Weight	0.5 kg

GSL 2 Professional**Surface Laser**

Technical data	
Part number	0 601 064 002
Working range	10 m
Levelling accuracy	0.3 mm/m
Laser Class	3R
Self-levelling range	±4°
Weight	5.77 kg

GOL 26 D Professional**Optical Level**

Technical data	
Part number	0 601 068 000
Magnification	26x
Working range	100 m
Levelling accuracy	± 0.2 mm/m
Tripod thread	5/8"
Weight	1.7 kg

GOL 32 D Professional**Optical Level**

Technical data	
Part number	0 601 068 500
Magnification	26x
Working range	100 m
Levelling accuracy	± 0.2 mm/m
Weight	1.7 kg

DNM 60 L Professional**Inclinometer**

Technical data	
Part number	0 601 014 000
Measurement range	0-360° (4x90°)
Electronics measurement accuracy 0°/90°	± 0.5°
Electronics measurement accuracy 1°- 89°	± 0.2°
Measurement accuracy, vials	± 0.057° = ± 1mm/m
Automatic deactivation facility, approx.	5 mins
Operating duration, approx.	200 h
Power supply	1 x 9 V 6LR61
Weight	0.7 kg

DNM 120 L Professional**Inclinometer**

Technical data	
Part number	0 601 014 100
Measurement range	0-360° (4x90°)
Electronics measurement accuracy 0°/90°	± 0.5°
Electronics measurement accuracy 1°- 89°	± 0.2°
Measurement accuracy, vials	± 0.057° = ± 1mm/m
Automatic deactivation facility, approx.	5 mins
Operating duration, approx.	200 h
Power supply	1 x 9 V 6LR61
Weight	1.3 kg



Scan with your
smartphone.



Explore the world of
Bosch Power Tools.

Bosch Limited, Power Tool Division,
PA-AT Complex, Hosur Road, Adugodi,
Bangalore – 560030.
Tel: 080-22996143. Fax: 080-22223742.

